





HOSES & HOSE KITS

1.6 HOSES & HOSE KITS

FIRE HOSE KITS

Hose Kits: Fire Quenchers both standard and deluxe

| | | | List price | |
|--|----------------|---|----------------|---|
| Standard | QFFKIT1 | <ul style="list-style-type: none"> 1 x 6m x 50mm suction hose fitted with 50mm nut & tail fitting & suction strainer 1 x 20m x 20mm discharge hose fitted with 25mm nut & tail & jet spray nozzle | \$362 |  <p>Standard fire hose kit</p> |
| Deluxe | QFFKIT3 | <ul style="list-style-type: none"> 1 x 6m x 50mm suction hose fitted with 50mm nut & tail fitting & suction strainer 2 x 20m x 20mm discharge hose fitted with 25mm nut & tail & jet spray nozzles | \$470 | |
| Fire Retardant Hose Kit with Storz fittings | QFFKIT4 | <ul style="list-style-type: none"> 1 x 6m x 50mm super elastic PVC suction hose with Storz fitting & suction strainer 1 x 30m x 35mm fire retardant percolating discharge hose with Storz fitting & high quality firefighting nozzle Includes Storz fittings for pump to connect Deluxe kit hoses ... <ul style="list-style-type: none"> 1½" (discharge hose connector) QSTORZ 1.5"F 2" (suction hose connector) QSTORZ2"X2"F | \$694 |  <p>Fire retardant fire hose kit with Storz fittings SAFER, SMARTER</p> |
| Fire hose reel kit | QFFKIT6 | <ul style="list-style-type: none"> 1 x 20m x 20mm discharge hose fitted with 25mm nut & tail & jet spray nozzle Galvanised hose reel with locking pin with brass swivel & grease nipple | \$1,109 | |



CONTRACTOR HOSE 1" - 6"



Suction Hose

- Type C female Camlock
- Strainer fitted

NOTE: needs to connect to Type A Camlock fitting on pump inlet, p25

| Hose dia | S/code (**= LENGTH, e.g . QPFGS3808F) | 6 MTR | 8 MTR | 10 MTR |
|----------|---------------------------------------|-------|-------|--------|
| 1" | QPFGS25**F | \$114 | \$125 | \$134 |
| 1½" | QPFGS38**F | \$114 | \$135 | \$155 |
| 2" | QPFGS50**F | \$151 | \$180 | \$209 |
| 3" | QPFGS76**F | \$279 | \$328 | \$376 |



Discharge Hose ... Blue Lay Flat (up to 75 psi)

- Type C female Camlock
- Type E male Camlock

Suit Aussie gushers
NOTE: needs to connect to Type A Camlock fitting on pump outlet, p25

| Hose dia | S/code (**= LENGTH, e.g . QLFH25BL015F) | Max working pressure psi | 10 MTR | 15 MTR | 20 MTR | 50 MTR | 100 MTR |
|----------|---|--------------------------|--------|--------|--------|---------|---------|
| 1" | QLFH25BL***F | 75 | \$61 | \$84 | \$96 | \$183 | \$328 |
| 1½" | QLFH38BL***F | 75 | \$70 | \$89 | \$110 | \$212 | \$376 |
| 2" | QLFH50BL***F | 65 | \$87 | \$111 | \$137 | \$289 | \$518 |
| 3" | QLFH75BL***F | 65 | \$163 | \$209 | \$254 | \$510 | \$905 |
| 4" | QLFH100BL***F | 65 | \$206 | \$259 | \$311 | \$626 | \$1,153 |
| 6" | QLFH150BL***F | 45 | \$534 | \$638 | \$743 | \$1,374 | \$2,424 |



Discharge Hose ... Red Lay Flat (up to 150 psi)

- Type C female Camlock
- Type E male Camlock

Suits high pressure pumps like Aussie fire pumps and Brigade Boss series (SL & SX)
NOTE: needs to connect to Type A Camlock fitting on pump outlet, p25

| Hose dia | S/code (**= LENGTH, e.g . QLFH25RL015F) | Max working pressure psi | 10 MTR | 15 MTR | 20 MTR | 50 MTR | 100 MTR |
|----------|---|--------------------------|--------|--------|--------|---------|---------|
| 1" | QLFH25RL***F | 150 | \$76 | \$95 | \$113 | \$223 | \$406 |
| 1½" | QLFH38RL***F | 150 | \$102 | \$127 | \$154 | \$308 | \$570 |
| 2" | QLFH50RL***F | 150 | \$129 | \$163 | \$199 | \$412 | \$763 |
| 3" | QLFH75RL***F | 130 | \$235 | \$296 | \$510 | \$719 | \$1,322 |
| 4" | QLFH100RL***F | 130 | \$353 | \$445 | \$540 | \$1,100 | \$2,035 |
| 6" | QLFH150RL***F | 100 | \$608 | \$752 | \$894 | \$1,751 | \$3,179 |