



Floodlight	Lumen	Light coverage
6x150W MultiLED	120.000 lm	4200 mq



Technical Specification	
Rated frequency	50 Hz
Rated Voltage	230 V
Rated Power	3.5 Kw
Operating temperature	-30/+50
Sound Level	61 dB
Control unit	DeepSea 3110
Auxiliary power	1.2 kVa
Engine	IL NVU
Model	Yanmar 2TNV70 Kohler KDW 702
Speed	1500 rpm
Coolant	Liquid
Cylinders	2
Emissions	Stage V
Alternator	Stage v
Model	Linz Alumen
Rated outlet	3.5 kVA
Regulation	Brushless
Voltage accurancy	+/- 5%
Energy consumption	
Fuel consumption	0,55 l/h
Tank	120
Fuel	Diesel
Running time	218 h
Galvanized mast	
Height	8.5 m
Mast	Hydraulic
Rotation	350°
Wind speed resistance	110 km/h
Canopy & Trailer	
Trailer	Road – tow trailer EU approved
Tyres	185/70/R13
Basement	Bunded base 120%
Stabilizers	4 + 1 (wheel)
Canopy	Powder coating paint
Optional	
Optional included as standard	Dusk to dawn sensor with Autostart
Shipment Dimension	225v147v240 cm
Weight	235x147x240 cm 850 kg
Truck	10
Container 40"	11
- Container TV	